# Investigating key performance indicators for facility management practices in university buildings in Minna, Nigeria

L.O. Oyewobi<sup>1</sup>, R. A. Jimoh<sup>2</sup>, B. Suleiman<sup>3</sup> and B. Ogundipe<sup>1</sup> <sup>1</sup>Department of Quantity Surveying, Federal University of Technology, Minna, <sup>2</sup>Department of Building, Federal University of Technology, Minna,

<sup>3</sup>Department of Quantity Surveying, University of Ilorin, Ilorin <sup>1</sup>Loyewobi@futminna.edu.ng; <sup>2</sup>rosney@futminna.edu.ng; <sup>3</sup>bolajisule1960@gmail.com

### Abstract

The aim of this paper is to identify the key performance indicators for facility management practices in university buildings in Minna in order to evaluate and improve on its management to enhance better performance. The research employed a quantitative approach with the occupants of the lecture rooms and office buildings as a unit of analysis. A total of 373 questionnaires were distributed to the end-users of the buildings. The paper revealed that existing performance evaluation of the university is weak and thus, the performances of the buildings were found to be average due to their age. The paper identified the key performance indicators for the management of university buildings, which is expected to enhance Building Performance Evaluation (BPE) for facility managers by taken into cognizance the key factors. The results of the research are important to the end-users as well as facility and maintenance managers in organisations. In addition, the output is also significant to those in academics as this may foster further research.

### Keywords

Building performance evaluation, educational buildings, facility management and key performance indicator

# 1. Introduction

Facilities management is not entirely a novel area of management in some developing world which although had existed in various units and under

various professions, it is only just being aggregated into a singular functional field of management. In Nigeria, facilities management is not an all comer's affair and it cannot be made so if appreciable results are to be expected with the sale of many Federal Government of Nigeria houses to the public; a challenge of facilities management has been thrown to the practitioners. A new line of business has also been opened to entrepreneurs, though many organizations and institutions as asserted by Lavy (2008) often fail to recognize the importance of facility management (FM) to their business performance and success. The goal however, must be to manage Nigeria's huge infrastructure portfolio successfully.

Okupe (2002) identifies professionals as the key participant in the construction industry as well as in the management department. Maintenance delayed is costlier. Every element in a facility should be covered by appropriate maintenance, determined by the management. The only way to prolong the life span of a house is to maintain it regularly which in turn enables the facility to fulfil its function. However, the cost of replacement of a home is several times the annual cost of maintenance required to keep the facility in use. Every facility is designed and built to meet a specific need or a group of needs, which must have been determined to a large extent before the implementation of the project. The ability of a facility to successfully accomplish the purpose for which it is designed is a measure of its success (Opaluwah, 2005). In Nigeria, according to Adenuga and Iyagba (2005) public buildings are in poor and deplorable conditions of structural and decorative disrepairs.

The smooth operation of the management of facilities (multiple or single) depends largely on the ability to determine an organic process as a driving vehicle for delivery. No matter how simple or complex a facility may be without a defined order of maintenance management, the facility shall sooner or later not only become non-functional but may in addition constitute a hazard for its users. Barrett (2000) supports the evaluation of user needs in order to action better conditions for them using a Post-Occupancy Evaluation (POE) process.

## 2. Literature Review

# **2.1** The Nigerian university and the state of infrastructure facilities

According to Akpanuko (2012), Nigerian university system has undergone a series of developmental phases which can satisfactorily measure up with what is obtainable in the other countries of the world. This growth has witnessed an increase in the number of Federal Government owned universities from 4 in 1960s to 38 Universities; 37 State Universities and 50 private universities (125 in total) (National University Commission [NUC], 2010). Over the last three decades, the number of students admitted to Nigerian universities has increased tremendously from fifty-five thousand students (55,000) in 1980 to over four hundred thousand students (400,000) in 2002 (Bollag, 2002). As the upsurge in the number of students admitted or seeking admission increase over the years, the existing facilities can hardly take 20% of the student Soludo (cited in Akpanuko, 2012), and this has resulted in complete decline and collapse of the system of education (Bollag, 2002). The situation is not anything better thirteen years later.

Olukoya (2006) asserted that a typical Nigerian university is characterised with overcrowded classrooms with students sitting on the windows of lectures halls during classes, as well as ill-equipped laboratories and libraries. Nwaopara et al. (2008) alluded to the fact that universities in Nigeria have been reduced to glorified secondary schools as a result of institutional decay and poor state of infrastructure facilities. The continuous decay and neglect of the university infrastructure and many other reasons advanced by the academic staff union of universities (ASUU) has led to incessant strike actions like six months' strike experienced in 2002 (Bollag, 2002) and other subsequent industrial action embarked by the unions over the years. Although Nigeria's budgeting for the education department is low, but governmental politicisation of university administration has increased level of corruptions and misappropriation of funds which invariably impact negatively on the state of infrastructure facilities. The paper argued that although number of students grows in geometrical progression without commensurate facilities, an organised facility management practices is capable of improving the deplorable state of the facilities and enhance its physical performance as well as improve the effectiveness with which the facilities are maintained and managed.

# **2.2** Probable causes of facilities management failure in operational life

### Lack of a policy

Facility management is not an ad-hoc exercise. There must be a concerned and systematic approach to the management of facilities in order for desired objectives to be realized. This therefore necessitates a policy, which either be documented or imbibed by all concerned and supported by management.

### Lack of funding

In most organizations, top management needs to be fully briefed in order to understand and appreciate the demands of Facility Management such organizations. While it might be obvious that broken down equipment need repairs, funds requested for preventive maintenance may need some explanation before release is made. Most administrators believe that a functioning facility/equipment needs no more funding than running input cost only. This attitude has resulted in many organizations embarking on breakdown maintenance as a maintenance policy. The shortcomings of this approach are obvious as such facilities no sooner begin to deteriorate appreciably.

### Use of unqualified personnel

Appropriate personnel are very crucial in the procurement of facilities management. While everyone appreciates a well-managed facility, only a few are professionally qualified to bring it about. The use of unqualified personnel is a ready source of disaster.

#### Abuse of facilities

Many users take liberties when occupying especially houses. They fail to realize that specific constants and values of loading/weights were employed in the design of these structures. Sometimes, this may be as a result of ignorance but suffice it to say that abuse of facilities is a potent cause of failures. Abuse occurs when a facility is subject to forces for which it was not designed or intended to resist.

### 2.2 Key Performance Indicators of Constructed facilities

Several research works have been carried out on success factors and success criteria for construction projects but those that dwell on constructed facilities are few in Nigeria. Though, for construction projects Cookie-Davies (2002)

distinguished between project success and project management success, the former is measured against the overall objectives of the project while the latter is measured against the widespread and traditional measures of performance against cost, time, and quality. Cookie-Davies (2002) argued that success factors are those which contribute to achieving success on a project while success criteria are the measures by which the success or failure of a project will be judged.

Few among those that examine the critical success factors of constructed facilities considered it from the angle of customer satisfaction as an addition to the traditional performance measurement of cost, time and quality (Torbica and Stroh, 2001; Karna et al., 2009). In a research carried out by Torbica and Stroh (2001) it was submitted that quality improvement effort will improve customer satisfaction when the efforts are geared towards a higher product and service quality. Toor and Ogunlana (2010) concluded that factors constituting the success criteria are commonly referred to as the key performance indicators or KPIs and it was observed that the KPIs are helpful to compare the actual and estimated performance in terms of effectiveness, efficiency and quality of both workmanship and product (Cox et al., 2003). Toor and Ogunlana (2010) differentiate between success factors and key performance indicator to give better understanding of the terminologies. Success factors are referred to as the efforts made or strategy adopted in achieving the desired success on project. Whereas, Key Performance Indicators are the compilations of data measures (either by quantitative or qualitative data) used to assess and evaluate the performance of the construction operation or constructed facilities (Toor and Ogunlana, 2010; Yuan et al., 2009).

Solomon and Young (2007) reported that performance objectives are the baseline in carrying out performance measurement in the process of determining how successful organizations or individuals have been in attaining these objectives. No two facilities are entirely the same in terms of condition and maintainability, thus, it seems difficult as every facility has certain unique features and limitations and therefore generalizing the taxonomy of KPIs for all kinds of facilities looks fairly impractical (Toor and Ogunlana, 2010). Therefore, there is need to identify and evaluate a set of common indicators to be used by facility manager and maintenance officers in measuring performance of facilities (Cox *et al.*, 2003).

# 3. Research Method

The study source data through questionnaire administered to the users of the facilities which include Staff (both academics and non- academic) and students drawn from various departments within the University environment. Data relating to the population of the study area were retrieved from the archive. Prior to collection of data, pilot test was conducted using the first drafted questionnaire to ensure that the research instrument would be well understood by the respondents to establish the most productive form of data analysis. The input and the results generated from the pilot study were used to refine the questionnaire before the wide survey was carried out. Reliability test was also conducted on the research instrument with respect to key performance indicator and the perception of end users on Building performance evaluation were found to be 0.93 and 0.77 respectively.

This attests to the reliability of the instruments used for the study. In order to have a defined sample size, the total population for this study include all registered students, academic and non-academic staff within the study area. The lists of the total academic staff, non-academic staff and students are as obtained from the Academic Planning Unit of the university. The total sampling frame for the study was of 612 for academic staff, 171 for non-academic staff and 12947 for all the students. The total number of students as at the 2010/2011 session being the period within which this research is being carried out was 12947 out of which 2106 were 100 level students, a difference which resulted to 10841, therefore the total sampling frame were 11624 for the study, 100 level students were left out because it was believed they do not have required familiarities/knowledge of the facilities on campus. Based on the sample frame, sample size in respect of the various categories of respondents was determined from the following formulae as used by Hogg and Tannis (1997):

$$M = \frac{Z^2 x P^* x (1 - P^*)}{E^2}$$
(1)

$$n = \frac{m}{1 + \frac{m-1}{N}}$$
(2)

2210

Where m= sample size of unlimited population, n= sample size of limited population, Z= value (1.96 for 95% confidence level, P= degree of variance between elements of population (0.5), E= minimum error on the point estimate.

Substituting the pre-determined variables, the sample size for each of the study population the respondents from academic staffs, non-academic staffs and students was determined to be 19, 7 and 347 respectively. The sample size for the various categories of respondents was therefore found to be 373. Based on the result of pilot test carried out, 84 questionnaires were administered to academic staff, 30 to non-academic staff and 259 to students summing up to 373 determined using the formulae above. This was done on the premises that both academic and non-academic staffs surveyed have stayed more than five years required by the students in pursuance of their degree certificate. The research adopted random sampling technique; in which case every respondent in the defined population was given equal chance during the administration of the questionnaire. The valid retrieved questionnaire with respect to the overall response to the survey comprised a total of 284 well completed questionnaires, representing approximately 76 % response rate and according to Idrus and Newman (2002), a response rate of 30% is good enough in construction studies, which is also in line with the submission of (Fellow & Liu, 1997; Akintove & Fitzgerald, 2000) that figure in the range of 20-30% response rate in questionnaire survey of the construction industry is good for analysis. The profiles of the respondents were analysed using percentiles. The key performance indicators were analysed using factor analysis, Mean score value was used in determining the strength and weakness of the indicator, Chi square was used to analyse the level of awareness among the respondents and finally, the building performance evaluation relativity was carried out using relative importance indices.

|      | 1 a          | 1 - 3 | unping | Traine Of | i Kespe | muents |      |       |
|------|--------------|-------|--------|-----------|---------|--------|------|-------|
| S/No | Respondents  | SAAT  | SEET   | SEMT      | SET     | SICT   | SSSE | TOTAL |
| 1    | Academic     | 93    | 150    | 12        | 109     | 43     | 205  | 612   |
| 2    | Non-Academic | 26    | 41     | 15        | 31      | 28     | 30   | 171   |
| 3    | Student      | 1207  | 3160   | 524       | 1690    | 519    | 3741 | 10841 |
|      | TOTAL        | 1326  | 3351   | 551       | 1830    | 590    | 3976 | 11624 |

Table 1 - Sampling Frame of Respondents

Oyewobi USEP: Journal of Research Information in Civil Engineering, Vol.15, No.3, 2018 et al

| S/No | Respondents  | SAAT | SEET | SEMT | SET | SICT | SSSE | TOTAL |
|------|--------------|------|------|------|-----|------|------|-------|
| 1    | Academic     | 3    | 4    | 1    | 3   | 2    | 6    | 19    |
| 2    | Non-Academic | 1    | 1    | 1    | 1   | 1    | 1    | 7     |
| 3    | Student      | 39   | 99   | 18   | 55  | 18   | 118  | 347   |
|      | TOTAL        | 43   | 104  | 20   | 59  | 21   | 126  | 373   |

Table 2: Sample size for the category of respondent

## 4. Data Analysis and Discussion

This section shows data analysis of the key performance indicators

### 4.1 Critical Performance Indicators (CPI) of university buildings

The factor analysis results show that the KMO of sampling accuracy and Bartlett's test of sphericity. The KMO was found to be 0.810 and 0.780 for student and staff respectively which is greater than 0.50 as a value less than this would be unacceptable for analysis. This means that the data is accurate for factor analysis. Similarly, the Bartlett's test was found to be significant which show that the data does not suffer from multi-collinearity.

# **4.2** Factor extractions for the CPI of university buildings (Student)

Table 3 shows all the possible number of factors which were extractible from the analysis of the elements for critical performance indicators of building performance for student respondents. The Eigen value, percentage of variance and cumulative percentage of variance of factors are also shown. Nevertheless, the important factors are those whose Eigen value are greater than or equal to 1 because a component with an Eigen value less than 1 is taken to be less important or of no use to the result. From table 4 six factors were generated with the Eigen value in a descending order i.e. 8.207 for factor 1 to 1.041 for factor 6. Which were selected based on the criteria of an Eigen value greater than 1. The chosen factor generates a percentage cumulative of 64%.

|  | Extraction % | Factor |        |          |         |
|--|--------------|--------|--------|----------|---------|
|  | Communalit   |        | Eigen  | % of     | Cumulat |
| Variable                               | У            |        | Value  | Variance | ive %   |
| Favourable learning                    | 52.9         | 1      | 8.207  | 32.828   | 32.828  |
| environment                            |              |        | 0.207  | 52.020   | 32.020  |
| Accessible classroom                   | 70.7         | 2      | 2.377  | 9.509    | 42.337  |
| Well ventilated                        | 70.1         | 3      | 1.853  | 7.414    | 49.750  |
| classroom                              |              |        | 1.055  | 7.414    | 47.750  |
| Adequate illumination                  | 63.6         | 4      | 1.413  | 5.652    | 55.402  |
| during day                             | <i>co i</i>  | -      |        |          |         |
| Adequate illumination                  | 68.4         | 5      | 1.1.56 | 4.626    | 60.028  |
| at night                               | 63           | 6      |        |          |         |
| Conducive classroom<br>for study       | 03           | 6      | 1.041  | 4.164    | 64.192  |
| Relatively close CR to                 | 75.1         | 7      |        |          |         |
| other amenities                        | 75.1         | /      | 0.980  | 3.918    | 68.110  |
| CR equipped with                       | 55.4         | 8      |        |          |         |
| building facilities                    |              |        | 0.899  | 3.596    | 71.706  |
| School library suitable                | 59.1         | 9      | 0.707  | 2 104    | 74.000  |
| for study                              |              |        | 0.796  | 3.184    | 74.890  |
| Standard library                       | 60.1         | 10     | 0.789  | 3.155    | 78.044  |
| building facilities                    |              |        | 0.789  | 5.155    | /8.044  |
| Standard clinic building               | 56.1         | 11     | 0.706  | 2.826    | 80.870  |
| facility                               |              |        |        |          |         |
| Standard laboratory                    | 65           | 12     | 0.623  | 2.492    | 83.362  |
| building facility                      | (7.)         | 12     |        |          |         |
| Standard sport facility                | 67.2         | 13     | 0.550  | 2.201    | 85.563  |
| Standard lecture halls                 | 67.3         | 14     | 0.510  | 2.040    | 87.603  |
| and theatres                           | 59.2         | 15     |        |          |         |
| CR protection against<br>harsh weather | 58.2         | 15     | 0.469  | 1.874    | 89.478  |
| Adequate fire-fighting                 | 74.3         | 16     |        |          |         |
| facilities                             | 74.5         | 10     | 0.410  | 1.641    | 91.119  |
| Building designed with                 | 51.9         | 17     |        |          |         |
| escape route                           | 01.7         |        | 0.378  | 1.511    | 91.630  |
| Rapid approach to                      | 71.5         | 18     | 0.000  | 1 251    | 02 001  |
| facility repair                        |              |        | 0.338  | 1.351    | 93.981  |
| Replacement of                         | 74.2         | 19     | 0.307  | 1.228    | 95.209  |
| damaged facility                       |              |        | 0.307  | 1.228    | 95.209  |
|  |              |        |        |          |         |

| Table 3 - Factor | Extractions | for the | CPI of | University | Buildings | (Student) |
|------------------|-------------|---------|--------|------------|-----------|-----------|
|                  |             |         |        |            |           |           |

2213

| Replacement with better facility        | 70.1 | 20 | 0.269 | 1.074 | 96.283  |
|---|------|----|-------|-------|---------|
| Checks carried out only<br>if reported  | 52.7 | 21 | 0.254 | 1.106 | 97.229  |
| Adequate building amenities             | 61.7 | 22 | 0.219 | 0.877 | 98.176  |
| Building amenities purpose satisfaction | 63.8 | 23 | 0.183 | 0.732 | 98.908  |
| Facility compared to other institution  | 68.8 | 24 | 0.164 | 0.658 | 99.566  |
| Innovative in facilities upgrade        | 63.5 | 25 | 0.109 | 0.434 | 100.000 |

#### 4.3 Factor extractions for the CPI of university buildings (Staff)

All the possible number of factors extractible from the analysis of the elements of building performance evaluation as responded to by the staff is as shown in Table 4. The Eigen value, percentage of variance and cumulative percentage of variance of factors are also shown. Nevertheless, the important factors are those whose Eigen value is greater than or equal to 1 because a component with an Eigen value less than 1 is taken to be less important or of no use to the result discussion. Seven factors were generated with the Eigen value in a descending order i.e. 7.561 for factor 1 to 1.033 for factor 7, (for the purpose of balancing both response from staff and student in this research factor seven was ignored). Which were selected based on the criteria of an Eigen value greater than 1.

|  |              |        |       | (        | ,      |
|--|--------------|--------|-------|----------|--------|
|  | Extraction % | Factor | Eigen | % of     | Cumula |
| Variable                               | Communality  |        | Value | Variance | tive % |
| Favourable learning<br>environment     | 76.1         | 1      | 7.561 | 30.246   | 30.246 |
| Accessible classroom                   | 89.4         | 2      | 4.096 | 16.384   | 46.630 |
| Well ventilated classroom              | 87.1         | 3      | 2.480 | 9.920    | 56.549 |
| Adequate illumination during day       | 94           | 4      | 2.293 | 9.170    | 65.720 |
| Adequate illumination at night         | 88.5         | 5      | 1.731 | 6.923    | 72.642 |
| Conducive classroom for study          | 81.3         | 6      | 1.449 | 5.796    | 78.438 |
| Relatively close CR to other amenities | 88.2         | 7      | 1.033 | 4.133    | 82.571 |

Table 4 Factor Extractions of CPI for evaluation of building performance (Staff)

| Oyewobi | USEP: Journal of Research Information in Civil Engineering, Vol.15, No.3, 2018 |
|---------|--|
| et al   |  |

| CR equipped with building                       | 75.6 | 8  | 0.960      | 3.841     | 86.413  |
|---|------|----|------------|-----------|---------|
| facilities<br>School library suitable for study | 85.7 | 9  | 0.795      | 3.182     | 89.594  |
| Standard library building facilities            | 91.6 | 10 | 0.552      | 2.208     | 91.802  |
| Standard clinic building facility               | 87.9 | 11 | 0.428      | 1.710     | 93.513  |
| Standard laboratory building facility           | 85.2 | 12 | 0.403      | 1.613     | 95.125  |
| Standard sport facility                         | 86.9 | 13 | 0.357      | 1.426     | 96.552  |
| Standard lecture halls and theatres             | 83.2 | 14 | 0.276      | 1.103     | 97.655  |
| CR protection against harsh weather             | 82.5 | 15 | 0.197      | 0.787     | 98.441  |
| Adequate firefighting facilities                | 93.8 | 16 | 0.133      | 0.533     | 98.975  |
| Building designed with escape route             | 77.1 | 17 | 0.101      | 0.405     | 99.380  |
| Rapid approach to facility repair               | 62.2 | 18 | 0.069      | 0.275     | 99.655  |
| Replacement of damaged facility                 | 86.1 | 19 | 0.056      | 0.223     | 99.878  |
| Replacement with better facility                | 79.7 | 20 | 0.024      | 0.095     | 99.973  |
| Checks carried out only if reported             | 74.9 | 21 | 0.007      | 0.027     | 100.000 |
| Adequate building amenities                     | 78   | 22 | 2.40E-016  | 9.58E-016 | 100.000 |
| Building amenities purpose satisfaction         | 91   | 23 | 3.20E-019  | 1.28E-018 | 100.000 |
| Facility compared to other institution          | 66.8 | 24 | -5.39E-017 | -2.16E016 | 100.000 |
| Innovative in facilities upgrade                | 71.5 | 25 | -3.09E-016 | -1.24E015 | 100.000 |

### 4.4 Factor rotation for KPI of building performance (Student)

Table 5 shows factor rotations for the student's population, various variables of critical performance indicators for the building performance evaluation (except for those less than 0.50) and communalities ( $h^2$ ) of factors attributing to the evaluation of building performance which was extracted from the rotated component matrix. These factor loadings are significant because the greater the value of the factor loadings, the more the variable contributes to that factor. Communalities ( $h^2$ ) describe the variance in the variables that have been accounted for by the factors extracted, 53%, 71%, 70%, 64, 68%,

63% of average communality in factor 1, factor 2, factor 3, factor 4, factor 5, and factor 6 respectively was accounted for by the factors extracted.

| Critical<br>Performance                                      | Variables  | Factor  | Extractions | Mean  | Cumulative |
|--|--|---------|-------------|-------|------------|
| Indicators   |  | loading | %           | Value | %          |
| Building<br>performance<br>Percentage                        | Favourable<br>learning<br>environment                              | 0.687   | 59.2        | 3.508 |            |
| variance<br>=32.828  | Standard clinic<br>building facility<br>Standard                   | 0.698   | 56.1        | 2.780 |            |
| Eigen value = 8.207  | laboratory<br>facilities<br>Standard sport                         | 0.658   | 65          | 2.601 |            |
|  | facilities<br>Standard lecture                                     | 0.776   | 67.2        | 3.031 |            |
|  | halls & theatres<br>Protection                                     | 0.654   | 67.3        | 2.977 |            |
|  | against harsh<br>weather<br>Adequate                               | 0.685   | 58.2        | 3.109 |            |
|  | building<br>amenities<br>Building<br>amenities                     | 0.676   | 61.7        | 2.659 |            |
|  | purpose<br>satisfaction<br>Facility                                | 0.656   | 63.8        | 2.752 |            |
|  | compared to<br>other institution<br>Innovative in                  | 0.702   | 68.8        | 2.954 |            |
|  | facilities upgrade   | 0.591   | 63.5        | 3.209 | 32.828     |
| Facility impact<br>& user safety<br>Percentage<br>variance = | Conducive<br>classrooms for<br>study<br>Classroom<br>equipped with | 0.631   | 63          | 2.837 |            |
| 9.509  | facilities   | 0.545   | 55.4        | 2.651 |            |
| Eigen value = 2.377  | Library suitable<br>for study<br>Standard library                  | 0.651   | 60.1        | 3.019 |            |
|  | building facilities  | 0.536   | 60.1        | 2.841 |            |
|  |  |         |             |       |            |

Table 5: Factor Rotation for CPI of Building Performance (student)

2216

|                   | Adequate fire-<br>fighting facilities | 0.637 | 74.3  | 2.516  |        |
|-------------------|---------------------------------------|-------|-------|--------|--------|
|                   | Building                              |       |       |        |        |
|                   | designed with<br>escape route         | 0.637 | 51.9  | 2.260  | 42.337 |
| Approach to       | Rapid approach                        | 0.037 | 51.7  | 2.200  | 42.337 |
| BPE               | to facilities repair                  | 0.659 | 71.5  | 2.558  |        |
| Percentage        | Replacement of                        | 0.057 | /1.5  | 2.330  |        |
| variance =        | damaged                               |       |       |        |        |
| 7.414             | facilities                            | 0.713 | 74.2  | 2.725  |        |
| /.414             | Replacement                           | 0.715 | /4.2  | 2.725  |        |
| Eigen value =     | with better                           |       |       |        |        |
| 1.853             | facilities                            | 0.763 | 70.1  | 2.624  | 49.75  |
| Building facility | Well ventilated                       | 0.705 | 70.1  | 2.021  | 19.15  |
| users value       | classrooms                            | 0.736 | 70.1  | 3.740  |        |
| Percentage        | Illuminated                           | 01120 | , 011 | 517 10 |        |
| variance =        | classroom during                      |       |       |        |        |
| 5.652             | day                                   | 0.786 | 63.6  | 3.841  |        |
|                   | Illuminated                           |       |       |        |        |
| Eigen value =     | classroom at                          |       |       |        |        |
| 1.413             | night                                 | 0.668 | 68.4  | 3.147  | 55.402 |
|                   | Accessible                            |       |       |        |        |
| Buildings         | classroom                             |       |       |        |        |
| accessibility     | locations                             | 0.708 | 70.7  | 3.774  |        |
| Percentage        | Relative close                        |       |       |        |        |
| variance =        | CR to other                           |       |       |        |        |
| 4.628             | amenities                             | 0.728 | 75.1  | 3.240  | 60.028 |
| Eigen value =     |                                       |       |       |        |        |
| 1.156             |                                       |       |       |        |        |
|                   | Checks carried                        |       |       |        |        |
| Facility          | out only if                           |       |       |        |        |
| maintenance       | reported                              | 0.635 | 52.7  | 3.442  | 64.192 |
| Percentage        |                                       |       |       |        |        |
| variance =        |                                       |       |       |        |        |
| 4.164             |                                       |       |       |        |        |
| Eigen value =     |                                       |       |       |        |        |
| 1.041             |                                       |       |       |        |        |

### 4.5 Factor rotation for KPI of building performance (Staff)

Table 6 shows factor rotations for staff population, the various variables for the BPE (except for those less than 0.50) and communalities ( $h^2$ ) of factors attributing to the evaluation of building performance which was extracted from the rotated component matrix. Communalities ( $h^2$ ) describe the variance in the variables that have been accounted for by the factors extracted, 76%, 89%, 87%, 94%, 89%, and 81% of average communality in factor 1, factor 2,

factor 3, factor 4, factor 5, and factor 6 respectively was accounted for by the factors extracted.

| Critical                   | 37                                  | Ender   | E (mathematic | Maria | C lut      |
|----------------------------|-------------------------------------|---------|---------------|-------|------------|
| Performance                | Variables                           | Factor  | Extractions   | Mean  | Cumulative |
| indicators                 |                                     | loading | %             | Value | %          |
| Building                   | Favourable learning                 |         |               |       |            |
| performance                | environment                         | 0.577   | 76.1          | 4.000 |            |
|                            | Standard clinic                     |         |               |       |            |
| Percentage of<br>explained | building facility                   | 0.518   | 89.9          | 3.000 |            |
| variance =                 | Standard laboratory                 |         |               |       |            |
| 30.246                     | facilities                          | 0.835   | 85.2          | 3.000 |            |
| Eigen Value =              | Standard sport                      |         |               |       |            |
| 7.561                      | facilities                          | 0.666   | 86.9          | 3.000 |            |
|                            | Standard lecture                    | 0.550   |               | 2 000 |            |
|                            | halls & theatres                    | 0.578   | 83.2          | 3.000 |            |
|                            | Protection against<br>harsh weather | 0.726   | 82.5          | 3.000 |            |
|                            | Adequate building                   | 0.726   | 82.3          | 5.000 |            |
|                            | amenities                           | 0.620   | 78            | 3.000 |            |
|                            | Building amenities                  | 0.020   | 78            | 5.000 |            |
|                            | purpose satisfaction                | 0.540   | 91            | 3.000 |            |
|                            | Facility compared                   |         |               |       |            |
|                            | to other institution                | 0.728   | 68.8          | 3.000 |            |
|                            | Innovative in                       |         |               |       |            |
|                            | facilities upgrade                  | 0.735   | 71.5          | 3.000 | 30.246     |
|                            | Conducive                           |         |               |       |            |
| User value and             | classrooms for                      |         |               |       |            |
| its impact                 | study                               | 0.837   | 81.3          | 3.000 |            |
|                            | Classroom equipped                  |         |               |       |            |
| Percentage of              | with facilities                     | 0.540   | 75.6          | 2.100 |            |
| explained                  | T '1 '4 11 C                        |         |               |       |            |
| variance =<br>16.384       | Library suitable for                | 0.616   | 85.7          | 2.500 |            |
| Eigen Value =              | study<br>Standard library           | 0.010   | 03.7          | 2.500 |            |
| 2.377                      | building facilities                 | 0.868   | 91.6          | 3.000 |            |
| 2.377                      | Adequate                            | 0.000   | 71.0          | 5.000 |            |
|                            | firefighting                        |         |               |       |            |
|                            | facilities                          | 0.816   | 93.8          | 3.000 |            |
|                            | Building designed                   |         |               |       |            |
|                            | with escape route                   | 0.783   | 77.1          | 2.000 | 42.337     |
| Approach to                | Rapid approach to                   |         |               |       |            |
| BPE                        | facilities repair                   | 0.520   | 62.2          | 2.000 |            |
|                            |                                     |         |               |       |            |

| Table 6 Factor Rotations for | Critical Performance    | Indicators of BPE ( | staff) |
|------------------------------|-------------------------|---------------------|--------|
| rable of actor Rotations for | Critical r critorinance | malcators of DI L ( | sum    |

| Percentage       |                     |       |      |       |        |
|------------------|---------------------|-------|------|-------|--------|
| variance =       | Replacement of      |       |      |       |        |
| 9.920            | damaged facilities  | 0.698 | 86.1 | 3.000 |        |
| Eigen Value =    | Replacement with    |       |      |       |        |
| 2.480            | better facilities   | 0.565 | 79.7 | 3.000 | 56.549 |
| Building         |                     |       |      |       |        |
| facility users   | Well ventilated     |       |      |       |        |
| safety           | classrooms          | 0.655 | 87.1 | 4.000 |        |
| Percentage       | Illuminated         |       |      |       |        |
| variance =       | classroom during    |       |      |       |        |
| 9.170            | the day             | 0.919 | 94   | 4.000 |        |
| Eigen value =    | Illuminated         |       |      |       |        |
| 2.293            | classroom at night  | 0.687 | 88.5 | 3.000 | 65.720 |
| Building         | Accessible          |       |      |       |        |
| facility upgrade | classroom locations | 0.941 | 89.4 | 4.000 |        |
| Percentage       |                     |       |      |       |        |
| variance =       | Relative close CR   |       |      |       |        |
| 6.923            | to other amenities  | 0.603 | 88.2 | 3.000 |        |
| Eigen value =    |                     |       |      |       |        |
| 1.731            |                     |       |      |       | 72.242 |
| Users changing   | Checks carried out  |       |      |       |        |
| needs            | only if reported    | 0.818 | 74.9 | 3.500 | 78.438 |
| Percentage       |                     |       |      |       |        |
| variance =       |                     |       |      |       |        |
| 5.796            |                     |       |      |       |        |
| Eigen value =    |                     |       |      |       |        |
| 1.449            |                     |       |      |       |        |

### 4.6 End users building performance perception

The variables were grouped into factors in descending rank order in Table 7, which were given headings under the critical performance indicators for educational buildings, from which conclusion were drawn for the six various factors, based on further analysis of each variables using the Mean to obtain the end users overall perceptions on the twenty-five (25) variables. Therefore, to obtain the populations perception on the various factors, the mean of each factor in Tables 5 and 6 for both staff and students were also obtained and are as follows:

CPI 1 was referred to as; Emphasis on building performance CPI 2 was referred to as; User value and its impact on Users CPI 3 was referred to as; Approach to building performance evaluation CPI 4 was referred to as; Building facility Users safety

### CPI 5 was referred to as; Building facilities upgrade CPI 6 was referred to as; Facility maintenance

| Table 7: End Users CPI of building performance perception |              |         |  |  |  |  |  |
|---|--------------|---------|--|--|--|--|--|
| Critical Performance Indicators                           | Average mean | Rating  |  |  |  |  |  |
| Emphasis on building performance                          | 3.029        | Average |  |  |  |  |  |
| User value and its impact on users                        | 2.644        | Low     |  |  |  |  |  |
| Approach to building performance evaluation               | 2.483        | Low     |  |  |  |  |  |
| Building facility users safety                            | 3.455        | Average |  |  |  |  |  |
| Building facilities upgrade                               | 3.504        | Average |  |  |  |  |  |
| Facility maintenance                                      | 3.471        | Average |  |  |  |  |  |
| Overall   | 3.097        | Average |  |  |  |  |  |

### Table 7: End Users CPI of building performance perception

#### Table 8: Relative important index of FM and BPE (Staff)

|                   |       |      | ·         | Standard  | Standard | · · ·    |          |
|-------------------|-------|------|-----------|-----------|----------|----------|----------|
| Variables         | RII   | Rank | Mean      | Deviation | Error    | Skewness | Kurtosis |
| Need for          |       |      |           |           |          |          |          |
| Building          |       |      |           |           |          |          |          |
| Performance       |       |      |           |           |          |          |          |
| Evaluation        | 86.92 | 2    | 4.3462    | 0.8458    | 0.16588  | -1.622   | 2.878    |
| Need for          |       |      |           |           |          |          |          |
| facility          |       |      |           |           |          |          |          |
| management        |       |      |           |           |          |          |          |
| department        | 89.23 | 1    | 4.4615    | 0.70602   | 0.13846  | -1.701   | 4.463    |
| better            |       |      |           |           |          |          |          |
| infrastructural   |       | -    |           |           |          |          |          |
| provision         | 82.31 | 3    | 4.1154    | 0.71144   | 0.13953  | -0.893   | 2.046    |
| Infrastructure    |       |      |           |           |          |          |          |
| purpose           |       |      |           | 1.0000    | 0.00155  | 0.405    | 1.001    |
| fulfilment        | 50.77 | 6    | 2.5385    | 1.02882   | 0.20177  | -0.127   | -1.086   |
| Incorporation     |       |      |           |           |          |          |          |
| of facility       |       |      |           |           |          |          |          |
| user's            | 45.20 | -    | 2 2 6 0 2 | 1 00221   | 0.10(57  | 0 101    | 1.007    |
| opinion<br>School | 45.39 | 7    | 2.2692    | 1.00231   | 0.19657  | -0.181   | -1.007   |
| facilities        |       |      |           |           |          |          |          |
| maintenance       | 55.39 | 5    | 2.7692    | 1.21021   | 0.23734  | -0.481   | -0.637   |
| Inquiry of        | 55.59 | 5    | 2.7092    | 1.21021   | 0.23734  | -0.461   | -0.037   |
| end user's        |       |      |           |           |          |          |          |
| opinion           | 71.54 | 4    | 3.5769    | 1.06482   | 0.20883  | -0.540   | -0.063   |
| opinion           | /1.54 | +    | 5.5709    | 1.00402   | 0.20885  | -0.540   | -0.003   |

# 4.7 Building performance evaluation and its relativity to facility management

The need for BPE, need for facility management department, better infrastructural provision, Infrastructure purpose fulfilment, Incorporation of facility users opinion, School facilities maintenance and Inquiry of end users opinion, had mean value of 4.4362, 4.4615, 4.1154, 2.5385, 2.2692, 2.7692, and 3.5769 respectively in Table 8 while in Table 9 the need for BPE, need for facility management department, better infrastructural provision, Infrastructure purpose fulfilment, Incorporation of facility users opinion, School facilities maintenance and Inquiry of end users opinion, School facilities maintenance and Inquiry of end users opinion had mean values of 4.22, 4.35, 4.24, 2.65, 2.57, 2.87 and 3.25 respectively.

|                           | Table 9: Relative important index (RII) of FM and BPE (Student) |      |      |           |          |          |          |
|---------------------------|---|------|------|-----------|----------|----------|----------|
|                           |   |      |      | Standard  | Standard |          |          |
| Variables                 | RII   | Rank | Mean | Deviation | Error    | Skewness | Kurtosis |
| Need for                  |   |      |      |           |          |          |          |
| Building                  |   |      |      |           |          |          |          |
| Performance               |   |      |      |           |          |          |          |
| Evaluation                | 84.42   | 3    | 4.22 | 0.86075   | 0.05359  | -1.217   | 1.823    |
| Need for                  |   |      |      |           |          |          |          |
| facility                  |   |      |      |           |          |          |          |
| management                |   |      |      |           |          |          |          |
| department                | 86.90   | 1    | 4.35 | 0.80441   | 0.05008  | -1.700   | 4.061    |
| Better                    |   |      |      |           |          |          |          |
| infrastructural           |   |      |      |           |          |          |          |
| provision                 | 84.88   | 2    | 4.24 | 0.77313   | 0.04813  | -1.369   | 3.460    |
| Infrastructure            |   |      |      |           |          |          |          |
| purpose                   |   |      |      |           | 0.05054  | 0.070    | 0.485    |
| fulfilment                | 53.02   | 6    | 2.65 | 1.18125   | 0.07354  | -0.362   | -0.677   |
| Incorporation             |   |      |      |           |          |          |          |
| of facility               | 51.40   | 7    | 0.57 | 1 17570   | 0.07220  | 0.510    | 0.624    |
| user's opinion            | 51.40   | 7    | 2.57 | 1.17570   | 0.07320  | -0.512   | -0.624   |
| School                    |   |      |      |           |          |          |          |
| facilities<br>maintenance | 57.44   | 5    | 2.87 | 1.30962   | 0.08153  | -0.270   | -1.133   |
| Inquiry of end            | 57.44   | 3    | 2.07 | 1.50962   | 0.08135  | -0.270   | -1.155   |
| user's opinion            | 65.00   | 4    | 3.25 | 1.21377   | 0.07557  | -0.465   | -0.641   |
| user s opinion            | 05.00   | 4    | 5.25 | 1.213//   | 0.07557  | -0.405   | -0.041   |

### 4.8 Extractions for Relative Importance Index for BPE and FM

It will be observed from Table 10 that highest level of importance was attached to building performance evaluation for the institution, next in ranking is better infrastructure provision, need for facility management, infrastructure purpose fulfilment, school facility management, inquiry of end

users' opinion, incorporation of Facility Users ideas in succeeding ranks. Likewise, from Table 10; the needs for facility management: such as better

|   | S   | taffs | Rank |      |  |
|---|-----|-------|------|------|--|
| BPE relativity to FM  | RII | Rank  | RII  | Rank |  |
| Need for BPE in this institution                                  | 89  | 1     | 87   | 1    |  |
| Better infrastructural provision                                  | 87  | 2     | 85   | 2    |  |
| Need for FM in this institution                                   | 82  | 3     | 84   | 3    |  |
| Infrastructure purpose fulfilment                                 | 72  | 4     | 65   | 4    |  |
| School facilities maintenance                                     | 55  | 5     | 57   | 5    |  |
| Inquiry of end user's opinion<br>Incorporation of facility user's | 51  | 6     | 53   | 6    |  |
| opinion   | 45  | 7     |      | 7    |  |

Table 10: Extraction for Relative importance index

infrastructural provision, need for building performance evaluation, and other functions of facility management in succeeding ranks. Hence, it can be inferred that there is a great relativity between building performance evaluation and facility management, as well as the need for facility management department for the institution whose functions are to carry out variable 1, 3,4,5,6 and 7 in the institution. Finally, the benefit of involving facility manager in the design and construction process as observed in variable 3 which were ranked 2.

The output of the paired sample t-test presented in Table 11 indicates that an insignificant difference exists between staff and students with respect to their perception on the performance of the buildings. The view of the respondent from staff and students confirms the insignificance regarding the performance evaluation of the buildings since value of t (24) = 1.068 and p > .05 in the frequency scale. Similarly, the paired sample correlation showed significant association in the opinion of the respondent since value of r = 0.587 and p < .05.

|      | Paired Differences                                    |       |           |         |            |         |       |     |         |
|------|---|-------|-----------|---------|------------|---------|-------|-----|---------|
|      | Std. 95% Confidence S<br>Std. Error Interval of the ( |       |           |         |            |         |       |     |         |
|      |   |       | Std.      | Error   | Interva    |         |       | (2- |         |
|      |   | Mean  | Deviation | Mean    | Difference |         | t     | df  | tailed) |
|      |   |       |           |         | Lower      | Upper   |       |     |         |
| Pair | Staff -   | -     |           |         | -          |         | -     |     |         |
| 1    | Student   | 0.084 | 0.39336   | 0.07867 | 0.24637    | 0.07837 | 1.068 | 24  | 0.296   |

 Table 11: Paired Samples Test

# **5. Discussion of findings**

Using the percentile for analysing the responses from end users it was deduced that majority of the staff i.e. 80.8% have idea on Building Performance Evaluation while 62.7% as of students have no idea on BPE, while the staff are highly aware of BPE the students have poorly oriented on building performance evaluation, but for a general conclusion it can be inferred that the users of building facilities are defectively oriented on BPE since the larger percent i.e. 90.8% of students as against 9.2% of staff have no BPE idea. This is in line with the findings by Cotts and Lee (1992) that organizations seem to have more information on items such as computers, photocopiers, refrigerators, etc, than their buildings and those that have a relatively good management of their assets, have little information concerning their building performance.

It will be observed that the highest of respondents of 66.7% and 76.9% who responded 'Yes' to idea on BPE were considered respectively, hence, deducing from their response the previous approach to BPE in the institution is weak. Affirming the findings of Mutlaq (2002); Amaratunga and Baldry (2000); Zimring and Rashidi (2008) that to date, little data is available in Africa to assess how extensively the use of the technique has diffused educational institutions, how it affects teaching spaces and overall organizational performance, also Leaman (2004) reports that the reason for this is because academic disciplines do not regard building performance as an area of legitimate interest.

In other to effectively investigate building performance it was imperative that the critical performance indicators were listed out and grouped under headings from which users view were analysed, the use of factor analysis and mean were applied, factor analysis was used to categorize the variables into

six sections out of which conclusions were drawn for the critical performance indicators for evaluation of educational buildings based on guidelines by the National University Commission (NUC), to draw conclusions for end users perception on the building facilities in the study area the Mean value of their response to each variable under each critical performance indicators was obtained , while the schools users value and approach to BPE were professed low, emphasis on building performance, building facilities users safety, building facility upgrade and facility maintenance were opined average, in all the critical performance indicators of building performance was found to be average, this fact is contrary with the findings of Okolie (2009) that Critical performance indicators are often absent in the design, construction and management of educational building facilities.

Building performance evaluation relativity to facility management was established with the use of the relative importance index were extracted, based on the level of importance attached to the dependent variables used for the analysis, it was deduced that building performance evaluation is related to facility management, there is a great need for facility management department in this institution for efficient building performance evaluation, and the benefits of the employing the Facility Manager for the maintenance of building facilities in this institution. This is similar to the findings of Preiser (2005) who postulated that Building performance evaluation is a diagnostic tool which allows facility managers to identify and evaluate critical aspects of a facility in order to develop design guidance and criteria for future facilities and that performance evaluation of buildings is a toolkit for facility managers, Barret and Baldry (2006). Building performance evaluation is a facilities management function and so the evaluation of buildings in terms of user-needs provides a platform for facility managers to make their contributions to the achievement of organizational goals

# 6. Conclusions

The study presented here investigated the key performance indicators for facility management practices in tertiary education buildings with a view to establishing critical performance indicators that will enhance Building Performance Evaluation (BPE) for facility managers by taken into cognizance the key factors. The study therefore concluded that most students have no idea on Building performance evaluation while most staff are highly

oriented on BPE idea. It was concluded that the institutions existing approach to building performance evaluation is weak. Hence, the buildings are found to be at average performance level. In view of these, the buildings being used as the case study for this research is an educational institution which still at its infrastructural development stage, hence, the best time to establish a facility management department for the institution which will raise the level of awareness of building performance evaluation among end users, by its periodical application to building facility evaluation, a task which will be carried out with response from end users, hence orienting them on BPE. This will ensure that facilities managers will procure and manage buildings using the critical performance indicators for educational buildings as recommended by the National University Commission. However, the establishment of a facility management department for the institution is paramount, so as to always be conversant with the building facilities end users ever dynamic needs in buildings. Hence, the need for a department which will be involved in the early design and construction of suitable building facilities for the institutions, effectively manage such in line with the user's vibrant needs, finally carryout the two functions above.

### References

Adenuga, O.A and Iyagba, R.O.A. (2005). Strategic Approach to Maintenance Practices for Public buildings in Lagos State. Journal of Environmental Studies, 5(1).

Akintoye, A. and Fitzgerald, E. (2000) A survey of Current Cost Estimating Practices in the UK. Construction Management and Economics, 18(2), 161-172.

Akpanuko, E. E. (2012), Tertiary Education Development and Sustainability in Nigeria: Beyond Financial Accountability. Journal of Economics and Sustainable Development, (3)8, 90-98.

Amaratunga, D (2000). Building Performance Evaluation in Higher Education Properties: A Facilities Management Approach, RICS Foundation, 3(14), 1-21.

Barret, P. and Baldry, D. (2003). Facilities management: Towards best practice. 2nd Edition., Blackwell Science.

Barrett, P (2000). Achieving strategic facilities management through strong relationships facilities 18(10//11/12), 421 - 426.

Bollag, B. (2002). Nigerian Universities Start to Recover from Years of Violence, Corruption and Neglect. The Chronicle of Higher Education A40-A42. Cookie-Davies, T., 2002. The real success factors on projects. International Journal of Project Management, 20(3), 185–190.

Cotts, D. and Lee, M. (1992), The facilities management hand book. New York. Amaloen; A division of American Management Association

Cox, R.F., Issa, R.R.A. and Aherns, D. (2003). Management's perception of key performance indicators for construction. Journal of Construction Engineering and Management, 129(2), 142–151.

Fellows, R. and Liu, A. (1997). Research Methods for Construction, Blackwell Science.

Hogg, R. V. and Tannis, E. A. (1997). Probability and statistical inferences. Prentice Hall

Idrus, A.B. and Newman, J.B. (2002). Construction related factors influencing the choice of concrete floor systems. Journal Construction Management and Economics, 20(1), 13-19.

Karna, S., Junnonen, J. and Sorvala, V. (2009). Modelling structure of customer satisfaction with construction. Journal of Facilities Management, 7 (2), 111-127

Lavy, S., (2008). Facility management practices in higher education buildings. Journal of Facilities Management, 6(4), 303-315.

Leaman, A. (2004). Post-Occupancy Evaluation: Building Use Studies [Online]. Available from: <u>www.usablebuildings.co.uk</u>. (Accessed 21 April 2011).

Mutlaq, M.A. (2002). A Study of the Relationship between School Building Conditions and Academic Achievement of Twelfth Grade Students in Kuwaiti Public High Schools. Unpublished PhD thesis. America: The Virginia Polytechnic Institute and State University.

National Universities Commission (NUC) (2010). List of Approved Universities in Nigeria. Monday. Bulletin, 5(11), 15p.

Nwaopara, A., Ifebhor, A., and Ohiwerei, F. (2008). Proliferating illiteracy in the Universities: A Nigerian perspective. International Journal for Educational Integrity, 4(1), 31-42.

Okolie, K. C (2009). Building performance evaluation in educational institutions: a case-study of universities in South 3East Nigeria, RICS COBRA Research Conference, University of Cape Town, 10-11th September 2009, 1598-1625.

Okorie, P.U. (2009). An Assessment of Accreditation Programmes of Nigerian Universities. Paper Presented at the Oxford Business and Economic Conference Programme held at St. Hugh's College Oxford: Oxford University. 24-26 June, 5-19.

Okupe, I. (2002) Private Sector Initiative in Housing Development in Nigeria – How flexible? Housing Today, 1, 21-26.

Olukoya, S. (2005). Africa: Universities that aren't worth the name. Retrieved January 27, 2007, from <u>http://medilinkz.org/news/news2.asp?newsID=9985</u>.

Opaluwah, S. A. (2005). Principles and Practices of Facility Management in Nigeria. Still Waters Publication.

Preiser, W. F. (2005). Building Performance Assessment: From Post-Occupancy Evaluation to Building Performance Evaluation. Architectural Science Review 48(2), 20-25.

Solomon, P.J. and Young, R.R. (2007). Performance-Based Earned Value, John Wiley & Sons, Inc., Hoboken.

Toor, S.R., Ogunlana, S.O. (2010). Beyond the 'iron triangle': Stakeholder perception of key performance indicators (KPIs) for large-scale public department development projects. International Journal of Project Management, 28,228–236.

Torbica, Z.M. and Stroh, R.C. (2001). Customer satisfaction in home building. Journal of Construction Engineering and Management. 127(1), 82-86.

Yuan, J., alex yajun Zeng, A. Y, Skibniewski, M. J and Li, Q. (2009). selection of performance objectives and key performance indicators in public–private partnership projects to achieve value for money. Construction Management and Economics, 27, 253–270.

Zimring, C. and Rashidi, M. (2008). Facility Performance Evaluation [Online]. Available from: <a href="https://www.wbdg.org/Resources/Fpe.Php">www.wbdg.org/Resources/Fpe.Php</a>. (Accessed 21 April 2011).